



Fan/Fixture Boxes ([View All](#) 4.OMB PDF)

[Previous Item](#)

[Next Item](#)

Fan & Fixture Mounting Boxes

Ceiling fan/fixture pan boxes.



| CATALOG NUMBER | UPC/DCI/NAED MFG #01 8997 | DESCRIPTION/STYLE | UNIT PKG | STD PKG | DIM A | DIM B | DIM C |
|----------------|---------------------------|---|----------|---------|-------|-------|-------|
| FB405 | 72185 | For 1/2" or 5/8" Drywall 6.0 Cu. In. | 25 | 25 | 2.315 | .570 | 4.250 |
| FB4050* | 28101 | For 1/2" or 5/8" Drywall 6.0 Cu. In. | 100 | 100 | 2.315 | .570 | 4.250 |
| FB407 | 72177 | For 5/8" Drywall 8.0 Cu. In. | 25 | 25 | 2.315 | .660 | 4.250 |
| FB4070* | 28102 | For 5/8" Drywall 8.0 Cu. In. | 100 | 100 | 2.315 | .660 | 4.250 |

Features and Benefits

- No loose parts to misplace – totally self-contained!
- Fan/fixture installation screws are "parked"...ready for easy fan/fixture bracket installation!
- Works well on double joists or wood I-beams
- Combination hex/Phillips head screws for easy installation with power screwdrivers
- 2-hour fire rating
- UL rated: 70 lb. fan, 200 lb. fixture; CSA rated: 50 lb. fan/fixture

*Bulk packing for lower cost.


Refer to chart on page N-15 for load ratings and number of single conductors.

PATENTED. ADDITIONAL PATENTS PENDING.



E170558 LR49636

Canadian orders ship with grounding lug required by CSA for use with fixtures.



Each fan/fixture box includes...

A ready-to-tighten center screw, installed NM cable connector, mud cover, second KO, and two screws for fan/fixture bracket installation (screwed in place until removed by installer).

Note: Install fan or fixture (not included) in accordance with manufacturer's instructions and all local applicable electrical codes, using the parked screws provided.

See Also:

- [Fan/Fixture Box Rating and # of Single Conductors](#)

[Home](#) | [Contents](#) | [Product Index](#) | [What's New](#)
[Samples](#) | [Local Reps](#) | [Contact Us](#)

Copyright © 2008. Arlington Industries. All rights reserved.