## **Arlington Industries, Inc.**



### SNAP<sup>2</sup>IT® **Connectors**

Zinc die-cast. For MC/HCF steel and aluminum cable • AC/HCF steel and aluminum cable • Flexible metal conduit steel and aluminum (regular and reduced wall) • MC cable continuous corrugated aluminum.









#### NO TOOLS!


- Safe and fast installations
- Saves about 17 seconds per fitting!
- Competitively priced

CATALOG NUMBER	UPC/DCI/NAED MFG #01 8997	TRADE Size	KO Size	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	DIM D	CABLE RANGE
38AST*	00070	3/8	1/2	50	500	1.410	.850	.405	1.000	.405612
38A*	00038	3/8	1/2	50	500	1.410	.850	.405	1.000	.405612
380ST	00381	3/8	1/2	50	500	1.280	.850	.400	1.000	.405612
380AST*	00382	3/8	1/2	50	500	1.280	.850	.400	1.000	.405612
45AST*	00045	1/2	1/2	50	500	1.660	1.130	.560	1.244	.590840

<sup>\*</sup>Provided with insulated throat.







#### With Insulated Throat and Red Tinted Inside Clip

CATALOG NUMBER	UPC/DCI/NAED MFG #01 8997	TRADE Size	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	DIM D	CABLE RANGE
40AST	00041	3/8	1/2	50	500	1.410	.850	.405	1.000	.485612
400AST	40347	3/8	1/2	50	500	1.280	.850	.400	1.000	.485612
50AST	72300	1/2	1/2	50	500	1.660	1.130	.560	1.244	.860920

Refer to chart on page E-25 for a list of cable types.

Concrete tight when taped.

Flexible metal conduit, CSA listed with anti-short bushing (UL not applicable).

SNAP-TITE® and SNAP<sup>2</sup>IT® products have been tested and listed by UL in accordance with UL's ground fault requirements. For additional information see page 6.

PATENTED. ADDITIONAL PATENTS PENDING.





#### SNAP<sup>2</sup>IT Connectors are EASY to Install...



**38AST** 



Just snap onto cable and snap into box!

# And EASY to Remove...



Using a screwdriver, lift the ring and twist off.







**40AST** 

RED TINTING means 'OPEN TANG' Design!

It gives you more room inside the fitting for easy insertion of wires.

The redesigned front end makes it easier than ever to snap the fitting into box!