



**SADDLEGRIP®**

**SNAP-TITE®**

**Connectors**

For aluminum and steel Flex • AC • MC cable. Zinc die-cast.



SG38AST



SG380AST

CATALOG NUMBER	UPC/DCI/NAED MFG #01 8997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	CABLE RANGE	END STOP DIAMETER
SG38AST*‡	80144	3/8	1/2	50	500	1.203	.555	1.077	.405-.612	.400
SG380AST*‡	80148	3/8	1/2	50	500	1.145	.555	1.077	.405-.612	.400 x .580
SG50ST‡	80150	1/2	1/2	50	500	1.458	.510	1.235	.710-.910	.620
SG50AST*‡	17501	1/2	1/2	50	500	1.145	.555	1.277	.710-.910	.620
SG75ST	18080	3/4	3/4	20	200	1.495	.510	1.570	.840-1.110	.820
SG75AST*	17755	3/4	3/4	20	200	1.540	.555	1.570	.840-1.110	.820

\*Provided with insulated throat.

‡Also for MCI-A (MC<sup>AP</sup>™ and HCF MC<sup>AP</sup>™) cable. Refer to page E-26 for cable ranges.

Refer to chart on page E-25 for a list of cable types.

Concrete tight when taped.

For cables smaller than .405" see L16 and L16ST on page E-5.

SNAP-TITE® products have been tested and listed by UL in accordance with UL's ground fault requirements. For additional information see page 6.

PATENTED.




E60812 LR49636



SG380AST

SG38AST



**Duplex**

**SADDLEGRIP®**

**SNAP-TITE®**

**Connectors**

Zinc die-cast. For aluminum and steel Flex • AC • MC cable • MCI-A (MC<sup>AP</sup>™ and HCF MC<sup>AP</sup>™) cable.



CATALOG NUMBER	UPC/DCI/NAED MFG #01 8997	TRADE SIZE	KO SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C	CABLE RANGE
SG3838ST	80152	3/8	1/2	25	100	.455	1.560	.780	(2) .445-.612
SG3838AST*	36210	3/8	1/2	25	100	.605	1.610	.780	(2) .445-.612

\*Provided with insulated throat.

Refer to chart on page E-24 for a list of cable types.

Refer to chart on page E-26 for MCI-A (MC<sup>AP</sup>™ and HCF MC<sup>AP</sup>™) cable ranges.

Concrete tight when taped.

With independent securing of the cables, you can use two different size cables.

SNAP-TITE® products have been tested and listed by UL in accordance with UL's ground fault requirements. For additional information see page 6.

PATENTED.



E60812 LR49636

