

Rigid/Intermediate Grade Conduit Fittings

- Clamps "Snap-On"
- Clamps
- Cable And Conduit Hangers

- Beam Clamps/Insulator Supports
- Conduit Clamps

CP

CP Rigid Intermediate

CLAMPS "SNAP-ON" - STEEL

UL File No. E-184283
(Heavy Gauge)

Application:

- To support rigid conduit and IMC to mounting service



Cat. #	Size	Unit Quantity	Standard Package	Weight Lbs. Per 100
410*	1/2"	100	500	5
411*	3/4"	100	500	6
412*	1"	50	250	11
413*	1 1/4"	50	250	13
414	1 1/2"	25	100	20
415	2"	25	25	22
206	2 1/2"	25	25	64
207	3"	25	25	71
208	3 1/2"	10	10	120
209	4"	10	10	130

* CSA Certified

CLAMPS - STEEL


(Light Gauge)



Cat. #	Conduit Size Rigid	Strap Size Inside	Unit Quantity	Standard Package	Weight Lbs. Per 100
566	1/4"	.540	500	500	2
567	3/8"	.675	200	1000	2

CABLE AND CONDUIT HANGERS - STEEL

With Bolts



Cat. #	Conduit Size Rigid	Conduit Size EMT	Unit Quantity	Standard Package	Weight Lbs. Per 100
0B	1/2"	3/8" & 1/2"	100	100	6
1-B	3/4"	3/4"	100	100	6
2-B	1"	1"	100	100	8
2 1/2-B	1 1/4"	—	100	100	10
3-B	1 1/2"	1 1/4"	100	100	11
4-B	—	1 1/2"	100	100	16
5-B	2"	2"	50	50	23
6-B	2 1/2"	2 1/2"	50	50	29
7-B	3"	3"	25	25	31
8-B	3 1/2"	3 1/2"	10	10	38
9-B	4"	4"	10	10	38

BEAM CLAMPS/INSULATOR SUPPORTS - MALLEABLE IRON

UL File No. E-184283

- Standard finish: Zinc Plated



Cat. #	Base Size	Jaw Open	Max. Wt. Support	Tapped Unit Qty.	Std. Pkg.	Wt. Lbs./100	
528*	3/4"	5/8"	230	10 - 24	25	100	14
529*	3/4"	5/8"	230	1/4" - 20	25	100	13
530	1"	3/4"	230	10 - 24	25	100	23
531	1"	3/4"	230	1/4" - 20	25	100	24
532	1 1/2"	3/4"	290	5/16" - 18	50	50	47
533	2"	7/8"	330	3/8" - 16	25	25	81
534	2 1/2"	7/8"	800	1/2" - 13	25	25	155

* Not UL listed

BEAM CLAMPS/INSULATOR SUPPORTS - STEEL



Cat. #	Base Size	Jaw Opening	Tapped Holes	Unit Qty.	Std. Pkg.	Weight Lbs. Per 100
529-S	3/4"	5/8"	1/4" - 20	50	50	13

CONDUIT CLAMPS

Application:

Right Angle - to attach the conduit run at a 90° angle to a beam or structural member

Right Angle Type - Electrogalvanized - Iron



Cat. #	Trade Size	Load Rating Lbs	Standard Package	Weight Lbs. Per 100
RAC50HD	1/2"	30	50	37
RAC75HD	3/4"	50	50	40
RAC100HD	1"	60	50	42
RAC125HD	1 1/4"	75	25	49
RAC150HD	1 1/2"	80	25	54
RAC200HD	2"	100	25	71
RAC250HD	2 1/2"	125	10	95
RAC300HD	3"	165	10	107
RAC350HD	3 1/2"	200	10	120
RAC400HD	4"	330	10	131

Application:

Parallel Type - to attach the conduit run parallel to a beam or structural member

Parallel Type - Electrogalvanized - Iron



Cat. #	Trade Size	Load Rating Lbs	Standard Package	Weight Lbs. Per 100
PARC50HD	1/2"	30	50	50
PARC75HD	3/4"	50	50	53
PARC100HD	1"	60	50	60
PARC125HD	1 1/4"	75	25	70
PARC150HD	1 1/2"	80	25	82
PARC200HD	2"	100	25	132
PARC250HD	2 1/2"	125	25	192
PARC300HD	3"	165	10	194
PARC350HD	3 1/2"	200	10	216
PARC400HD	4"	330	10	232

CONDUIT CLAMPS

Applications:

Edge Type - to attach the conduit run at a 90° angle to a thin beam or structural member.

Edge Type - Electrogalvanized - Iron



Cat. #	Trade Size	Standard Package	Weight Lbs. Per 100
ETC50HD	1/2"	50	63
ETC75HD	3/4"	50	69
ETC100HD	1"	50	82
ETC125HD	1 1/4"	25	95
ETC150HD	1 1/2"	25	108
ETC200HD	2"	25	121
ETC250HD	2 1/2"	25	153
ETC300HD	3"	10	214

Conduit Beam Clamp - J Type - Iron

UL File No. E-184283



Cat. #	Size	Max Weight Support	Unit Qty.	Std. Pkg.	Weight Lbs. Per 100
JCC1	1/2"	150	25	25	35
JCC2	3/4"	150	25	25	43
JCC34	1" & 1 1/4"	225	10	10	90
JCC56	1 1/2" & 2"	300	5	5	190
JCC78	2 1/2" & 3"	500	2	2	380
JCC910	3 1/2" & 4"	700	2	2	575