

Non-Metallic, Armored Cable, and Flexible Metallic Conduit Fittings

- Non-Metallic Sheathed Cable and Portable Cord Connectors
- Non-Metallic Sheathed Cable Connectors
- Armored Cable and Flexible Metallic Conduit Connectors
- Armored Cable and Flexible Metallic Conduit Connectors
- Armored, Metal Clad, and Non-Metallic Cable, and Flexible Metallic Conduit
- Flexible Metallic Conduit Connectors

NON-METALLIC SHEATHED CABLE AND PORTABLE CORD CONNECTORS – MALLEABLE IRON

Clamp Type

UL File No. E-22132

| Cat. # | K.O. Size | Clamp Opening Min. | Clamp Opening Max. | Unit Width | Unit Qty | Std Pkg | Wt Lbs./100 |
|--------|-----------|--------------------|--|------------|----------|---------|-------------|
| 631 | 3/4" | 33/64" | 13/16" | 13/16" | 20 | 200 | 14 |
| | | | For 2 conductor No.'s 8, 6 3 conductor No.'s 8, 6 | | | | |
| 632 | 1" | 3/8" | 1 1/64" | 1 1/64" | 10 | 100 | 21 |
| | | | For 2 conductor No.'s 8, 6 3 conductor No.'s 8, 6 | | | | |

NON-METALLIC SHEATHED CABLE CONNECTORS – DIE CAST ZINC

UL File No. E-10438

| Cat. # | Trade Size | K.O. Size | Unit Qty | Std Pkg | Weight Lbs. Per 100 |
|--------|------------|-----------|--|---------|---------------------|
| 759DC | 3/8" | 1/2" | 100 | 1000 | 4 |
| | | | For 2 conductor No.'s 14, 12, 10 3 conductor No.'s 14, 12 | | |
| 2631 | 3/4" | 3/4" | 50 | 500 | 9 |
| 2632 | 1" | 1" | 25 | 250 | 12 |
| | | | For 3 conductor No.'s 8, 6 | | |
| 2633 | 1 1/4" | 1 1/4" | 10 | 100 | 22 |
| | | | For 3 conductor No.'s 6, 4 | | |
| 2670 | 1 1/2" | 1 1/2" | 5 | 50 | 25 |
| | | | For 3 conductor No.'s 3, 2 | | |
| 2671 | 2" | 2" | 10 | 40 | 40 |
| | | | For 3 conductor No. 2/0 For 3 conductor No. 4/0 | | |

ARMORED CABLE AND FLEXIBLE METALLIC CONDUIT CONNECTORS – MALLEABLE IRON

Set Screw Type

UL File No. E-19188

| Cat. # | Trade Size | Diam. of Opening for Cable | Diam. of Bushed Hole | Unit Qty | Std Pkg | Wt Lbs./100 |
|--------|------------|----------------------------|--|----------|---------|-------------|
| 702-V | 3/8" | 5/8" | 7/16" | 100 | 500 | 7 |
| | | | For 2 conductor No.'s 14, 12 3 conductor No.'s 14, 12 4 conductor No. 14, 5/16" flex | | | |

QUICK-LOK® CONNECTORS FOR ARMORED AND METAL CLAD CABLE AND FMC – STEEL

| Cat. # | Trade Size | Unit Qty. | Std. Pkg. | Wt. Lbs./100 |
|--------|-------------|--|-----------|--------------|
| QLK50S | 1/2" single | 50 | 500 | 9 |
| | | For 14/4 to 10/3 For 3/8" FMC | | |
| QLK75 | 3/4" | 25 | 250 | 11.5 |
| | | For 10/3 to 6/3 For 3/8" and 1/2" FMC | | |
| QLK50D | 1/2" duplex | 25 | 250 | 11 |
| | | For 14/4 to 10/3 | | |

ARMORED CABLE AND FLEXIBLE METALLIC CONDUIT CONNECTORS – MALLEABLE IRON

Duplex Type

UL File No. E-19188

| Cat. # | Trade Size | Diam. of Opening for Cable | Diam. of Bushed Hole | Unit Qty | Std Pkg | Wt Lbs./100 |
|--------|------------|----------------------------|----------------------|----------|---------|-------------|
| 699* | 3/8" | 5/8" | 9/16" | 25 | 100 | 20 |

ARMORED, METAL CLAD, AND NON-METALLIC CABLE, AND FLEXIBLE METALLIC CONDUIT – DIE CAST ZINC

Duplex Type

UL File No. E-19188

| Cat. # | Trade Size | Diam. of Opening for Cable | Diam. of Bushed Hole | Unit Qty | Std Pkg | Wt Lbs./100 |
|--------|------------|----------------------------|----------------------|----------|---------|-------------|
| 2699* | 3/8" | 5/8" | 9/16" | 25 | 250 | 13 |

* UL Listed as grounding means under NEC 350-5 and suitable for hazardous location use per Class I, Division 2, NEC 501-4(b).

FLEXIBLE METALLIC CONDUIT CONNECTORS – MALLEABLE IRON

Squeeze Type

UL File No. E-19189

| Cat. # | Trade Size | Diam. of Opening for Cable | Diam. of Bushed Hole | Unit Qty | Std Pkg | Wt Lbs./100 |
|--------|------------|----------------------------|----------------------|----------|---------|-------------|
| 707 | 3/8" | 5/8" | 3/8" | 100 | 500 | 7 |
| | | | 1/2" | 15/16" | 50 | 200 |
| 708 | 3/4" | 1 1/8" | 3/4" | 20 | 100 | 22 |
| | | | 1" | 1 3/8" | 20 | 100 |
| 710 | 1 1/4" | 1 21/32" | 1 5/16" | 10 | 50 | 46 |
| | | | 1 1/2" | 1 7/8" | 5 | 25 |
| 712 | 2" | 2 1/2" | 2" | 2 | 10 | 101 |
| | | | 2 1/2" | 2 7/8" | 2 | 10 |
| 715 | 3" | 3 3/16" | 3" | 1 | 5 | 220 |
| | | | 3 1/2" | 4" | 1 | 1 |
| 722 | 4" | 4 19/32" | 3 31/32" | 1 | 1 | 610 |

Straight – Insulated

UL File No. E-19189

| Cat. # | Trade Size | Diam. of Opening for Cable | Diam. of Bushed Hole | Unit Qty | Std Pkg | Wt Lbs./100 |
|--------|------------|----------------------------|----------------------|----------|---------|-------------|
| 1708 | 3/8" | 5/8" | 3/8" | 100 | 500 | 8 |
| | | | 1/2" | 1 5/16" | 50 | 200 |
| 1712 | 3/4" | 1 1/8" | 3/4" | 20 | 100 | 17 |
| | | | 1" | 1 3/8" | 20 | 100 |
| 1711 | 1 1/4" | 1 21/32" | 1 5/16" | 10 | 50 | 42 |
| | | | 1 1/2" | 1 7/8" | 5 | 25 |
| 1713 | 2" | 2 1/2" | 2" | 2 | 10 | 100 |
| | | | 2 1/2" | 2 7/8" | 2 | 10 |
| 1715 | 3" | 3 3/16" | 3" | 1 | 5 | 221 |
| | | | 3 1/2" | 4" | 1 | 1 |
| 1722 | 4" | 4 19/32" | 3 31/32" | 1 | 1 | 610 |

* UL Listed flexible metallic conduit fittings are suitable as grounding means under NEC 350-5 and suitable for hazardous location use per Class I, Division 2, NEC 501-4(b).