

TINNED COPPER SPLICES - SC SERIES - STANDARD BARREL



Produced from high conductivity copper tubing. Serrations indicate proper crimp locations. Tin-plated to provide corrosion resistance. Marked with die index and color coded. Suitable for use at voltages up to 35 KV provided connector is properly taped. 5 KV is the maximum voltage in all bare splice applications.

CATALOG NO.	UPC CODE	WIRE SIZE	COLOR CODE	INSTALLING DIES	LENGTH	I.D.	O.D.	CTN. QTY.	SHPG. WT. LBS./100
SC-8	03700	8	red	1-21	.90	.17	.27	100	1.4
SC-6	03701	6	blue	2,7/374,24	1.00	.20	.30	100	2.2
SC-4	03702	4	gray	3,8/346,29	1.00	.25	.34	100	2.6
SC-3	03703	3	brown	-,9,33	1.25	.31	.42	50	3.4
SC-2	03704	2	brown	4,10,33	1.25	.31	.42	50	4
SC-1	03705	1	green	4,11/375,37	1.80	.36	.47	50	5.2
SC-1/0	03706	1/0	pink	5,12/348,42	1.60	.39	.52	50	5.7
SC-2/0	03707	2/0	plack	6,13,45	1.75	.44	.56	25	6.5
SC-3/0	03708	3/0	orange	9,14,50	1.75	.49	.62	25	7.7
SC-4/0	03709	4/0	purple	10,15,54	1.90	.55	.69	25	8
SC-250	03710	250	yellow	11,16,62	2.00	.59	.75	25	12
SC-300	03711	300	white	12,17/298,66	2.10	.66	.81	12	14
SC-350	03712	350	red	13,18/324,71	2.10	.70	.87	12	18
SC-400	03713	400	blue	14,19/470,76	2.30	.76	.95	6	22
SC-500	03714	500	brown	15,20/299,87	2.50	.83	1.06	6	35
SC-600	03715	600	green	16,22/472,94	2.50	.93	1.19	6	48
SC-750	03716	750	black	17,24/473,106	3.21	1.03	1.31	3	56

TINNED COPPER SPLICES - C SERIES - LONG BARREL



Produced from high conductivity copper tubing. Serrations indicate proper crimp locations. Tin-plated to provide corrosion resistance. Marked with die index and color coded. Suitable for use at voltages up to 35 KV provided connector is properly taped. 5 KV is the maximum voltage in all bare splice applications.

CATALOG NO.	UPC CODE	WIRE SIZE	COLOR CODE	INSTALLING DIES	LENGTH	I.D.	O.D.	CTN. QTY.	SHPG. WT. LBS./100
C-8	03749	8	red	1-21	1.75	.17	.27	100	4
C-6	03750	6	blue	2,7/374,24	1.75	.20	.30	100	4
C-4	03751	4	gray	3,8/346,29	1.75	.25	.34	100	5.2
C-2	03753	2	brown	4,10,33	1.90	.31	.42	50	7.8
C-1	03754	1	green	4,11/375,37	2.20	.36	.47	50	10
C-1/0	03755	1/0	pink	5,12/348,42	2.20	.39	.52	50	11
C-2/0	03756	2/0	black	6,13,45	2.25	.44	.56	25	12
C-3/0	03757	3/0	orange	9,14,50	2.25	.49	.62	25	15
C-4/0	03758	4/0	purple	10,15,54	2.75	.55	.69	25	16
C-250	03759	250	yellow	11,16,62	3.25	.59	.75	25	25
C-300	03760	300	white	12,17/298,66	3.50	.66	.81	12	26
C-350	03761	350	red	13,18/324,71	3.75	.70	.87	12	31
C-400	03762	400	blue	14,19/470,76	3.75	.76	.95	6	37
C-500	03763	500	brown	15,20/299,87	4.25	.83	1.06	6	57
C-600	03764	600	green	16,22/472,94	4.50	.93	1.19	6	78
C-750	03765	750	black	17,24/473,106	4.75	1.03	1.31	3	102
C-1000	03766	1000	white	19,27,125	6.13	1.15	1.50	3	140