

SINGLE LUG - CU - EXTRUDED STYLE



Solid one-piece copper connector made from extruded copper for superior mechanical strength and excellent electrical performance. Steel screw. Suitable for use with copper wire only. Rated 600 volts.

CATALOG NO.	UPC CODE	WIRE RANGE CU-AL	LENGTH	HEIGHT	WIDTH	MTG. HOLE	CARTON QTY.	SHPG. WT. LBS./100
6TC	00500	6-14	1.020	.400	.375	.193	100	3
4TC	00501	4-14	1.075	.440	.450	.265	100	4
2TC	00502	2-14	1.125	.484	.458	.265	100	5
0TC	00503	1/0-14	1.277	.660	.548	.265	50	8
4/0TC	00504	4/0-2	1.950	.950	.812	.390	25	13

SINGLE LUG - CU - TUBULAR STYLE



Copper connector made from tubular copper. Steel screw. Suitable for use with copper wire only. Rated 600 volts.

CATALOG NO.	UPC CODE	WIRE RANGE CU-AL	LENGTH	HEIGHT	WIDTH	MTG. HOLE	CARTON QTY.	SHPG. WT. LBS./100
6TC-1	00505	6-14	.995	.778	.345	.203	100	2.1
4TC-1	00506	4-14	1.255	.831	.453	.258	100	3.5

SINGLE AND DOUBLE SOLDERLESS LUGS



Made of 99.98% pure electrolytic copper. Steel-plated screws to prevent rusting. 25 to 70 ampere size have slotted head screws. Larger sizes have hex head screws. Rated 600 volts.

CATALOG NO.	UPC CODE	FIG.	WIRE RANGE	MTG. HOLE	AMPERE RATING	CARTON QTY.	SHPG. WT. LBS./100
DE 703	00510	1	10-14	1/8	25	100	1.3
DE 704	00511	1	6-14	3/16	35	100	2.3
DE 705	00512	1	2-8	1/4	70	100	5.1
DE 711	00513	1	4-14	1/4	70	50	3.2
DE 706	00514	1	1/0-6	1/4	125	25	10.8
DE 713	00515	1	3/0-4	3/8	175	18	17
DE 707	00516	1	4/0-2	5/16	225	15	24.7
DE 710	00517	1	350-1/0	3/8	300	10	50
DE 708	00518	1	500-4/0	3/8	400	2	79.8
DE 709	00519	1	1000-600	1/2	650	2	202.0
D 899	00520	2	4/0-2	3/8	450	6	60
D 900	00521	2	350-1/0	3/8	600	6	100
D 901	00522	2	500-1/0	1/2	800	3	155
DE 713SP*	00525	*	3/0-4	3/8	175	18	18

*DE 713SP is plated and is supplied with a straight tang.