

STANDARD CABLE TIES (NATURAL)



Designed for quick and easy use. Strong and flexible, they can be wrapped around a bundle quickly and the tail easily inserted into a self-locking head. The smaller standard size ties even have bent tails to facilitate rapid tail-to-head insertion by user. Made of high-strength Nylon 66 that resists abrasion and chemicals such as common oils, greases,

solvents, dilute acids and alkalines. They are fungus-resistant, self-extinguishing and have excellent dielectric properties. Designed for continuous use from -40°F to 185°F (-40°C to 85°C) and will withstand temperatures up to 300°F (149°C). 94V-2 flammability rating.

CATALOG NO.	UPC NO.	(INCHES)		MAX. BUNDLE DIA.	MIN. TENSILE STRENGTH	PACKAGING		SHPG WT. LBS./100	
		LENGTH	WIDTH			STD. PKG.	STD. CTN.		
540	04192	5.5	.130	1 3/8	40 lbs.	100	3,000	0.15	Intermediate Duty
540X	04193	5.5	.130	1 3/8	40 lbs.	1,000	3,000	0.15	
750	05002	7.5	.187	2	50 lbs.	100	3,000	0.29	
750X	05061	7.5	.187	2	50 lbs.	1,000	3,000	0.29	Standard Duty
1150	05005	11	.187	3 1/8	50 lbs.	100	3,000	0.48	
1150X	05062	11	.187	3 1/8	50 lbs.	1,000	3,000	0.48	
1450	05006	14.5	.187	4	50 lbs.	100	3,000	0.60	Heavy Duty
1450X	05063	14.5	.187	4	50 lbs.	1,000	3,000	0.60	
24175	05010	24	.315	7 1/4	175 lbs.	50	500	2.56	

UV AND WEATHER RESISTANT CABLE TIES (BLACK)



Weather resistant cable ties are made from weather resistant Nylon 66. For applications exposed to outside elements. Good UV

resistance. Same temperature and flammability rating as natural ties. Available in black only.

CATALOG NO.	UPC NO.	(INCHES)		MAX. BUNDLE DIA.	MIN. TENSILE STRENGTH	PACKAGING		SHPG WT. LBS./100	
		LENGTH	WIDTH			STD. PKG.	STD. CTN.		
5400	04186	5.5	.130	1 3/8	40 lbs.	100	3,000	0.15	Intermediate Duty
5400X	04187	5.5	.130	1 3/8	40 lbs.	1,000	3,000	0.15	
7500	05022	7.5	.187	2	50 lbs.	100	3,000	0.29	
7500X	05123	7.5	.187	2	50 lbs.	1,000	3,000	0.29	Standard Duty
11500	05025	11	.187	3 1/8	50 lbs.	100	3,000	0.48	
11500X	05064	11	.187	3 1/8	50 lbs.	1,000	3,000	0.48	
14500	05026	14.5	.187	4	50 lbs.	100	3,000	0.60	Heavy Duty
14500X	05126	14.5	.187	4	50 lbs.	1,000	3,000	0.60	
241750	05030	24	.315	7 1/4	175 lbs.	50	500	2.56	

STANDARD MOUNTABLE (NATURAL)



Standard mountable cable ties are manufactured from natural Nylon 66 and complete with a mounting hole. Designed for continuous use from -40° F to 180° F (-40°C to 85°C). 94V-2 flammability rating. Black weather resistant

mountable cable ties are also screw mounted, they are manufactured from weather resistant Nylon 66 and suitable for outdoor use.

Designed for continuous use from -40°F to 185°F (-40°C to 85°C). 94V-2 flammability rating.

CATALOG NO.	UPC CODE	LENGTH	WIDTH	MAX. BUNDLE DIA.	MIN. TENSILE STRENGTH	MTG. HOLE	PACKAGING		SHPG WT. LBS./100
							STD. PKG.	STD. CTN.	
530MH	05050	6	.145	1 1/2	40 lbs.	.187	100	1,000	0.45
750MH	05051	8	.165	2 1/4	50 lbs.	.181	100	1,000	0.76
1150MH	05052	11.75	.188	3 1/4	50 lbs.	.191	100	1,000	1.04
1450MH	05053	14.5	.188	4	50 lbs.	.187	100	500	1.58
14120MH	05054	15.5	.310	4 3/4	120 lbs.	.240	100	500	1.77

WEATHER RESISTANT MOUNTABLE (BLACK)

CATALOG NO.	UPC CODE	LENGTH	WIDTH	MAX. BUNDLE DIA.	MIN. TENSILE STRENGTH	MTG. HOLE	PACKAGING		SHPG WT. LBS./100
							STD. PKG.	STD. CTN.	
5300MH	05055	6	.145	1 1/2	40 LBS.	.187	100	1,000	0.45
7500MH	05056	8	.165	2	50 LBS.	.181	100	1,000	0.76
11500MH	05057	11.75	.188	3 1/4	50 LBS.	.191	100	1,000	1.04
14500MH	05058	14.5	.188	4	50 LBS.	.187	100	500	1.58
141200MH	05059	15.5	.310	4 3/4	120 LBS.	.240	100	500	1.77