



Cable Ties

UV AND WEATHER RESISTANT

UV AND WEATHER RESISTANT CABLE TIES (BLACK)



Weather resistant cable ties are made from weather resistant Nylon 66. For applications exposed to outside elements. Good UV resistance. Same temperature and flammability rating as natural ties. Available in black only.

CATALOG NO.	UPC CODE	(INCHES)		MAX. BUNDLE DIA.	MIN. TENSILE STRENGTH	PACKAGING		SHPG WT. LBS./100	
		LENGTH	WIDTH			STD. PKG.	STD. CTN.		
4180	05020	4	.100	7/8	18 lbs.	100	5,000	0.08	Miniature
4180X	05122	4	.100	7/8	18 lbs.	1,000	5,000	0.08	
5180	05134	5.5	.100	1 3/8	18 lbs.	100	5,000	0.10	
5180X	05135	5.5	.100	1 3/8	18 lbs.	1,000	5,000	0.10	
8180	05023	8	.100	2 1/8	18 lbs.	100	3,000	0.15	
8180X	05124	8	.100	2 1/8	18 lbs.	1,000	3,000	0.15	
5400	04186	5.5	.130	1 3/8	40 lbs.	100	5,000	0.15	Intermediate Duty
5400X	04187	5.5	.130	1 3/8	40 lbs.	1,000	5,000	0.15	
8400	05024	8	.140	2 1/8	40 lbs.	100	3,000	0.24	
8400X	05069	8	.140	2 3/8	40 lbs.	1,000	3,000	0.24	
11400	05139	11.5	.140	3 1/4	40 lbs.	100	2,000	0.33	Standard Duty
4500	05085	4.75	.187	1 1/8	50 lbs.	100	5,000	0.17	
4500X	05136	4.75	.187	1 1/8	50 lbs.	1,000	5,000	0.17	
6500	05137	6.25	.187	1 5/8	50 lbs.	100	3,000	0.26	
6500X	05138	6.25	.187	1 5/8	50 lbs.	1,000	3,000	0.26	
7500	05022	7.5	.187	2	50 lbs.	100	3,000	0.29	
7500X	05123	7.5	.187	2	50 lbs.	1,000	3,000	0.29	
8500	05090	8	.187	2 1/8	50 lbs.	100	3,000	0.33	
8500X	05019	8	.187	2 1/8	50 lbs.	1,000	3,000	0.33	
11500	05025	11	.187	3 1/8	50 lbs.	100	3,000	0.48	
11500X	05064	11	.187	3 1/8	50 lbs.	1,000	3,000	0.48	
14500	05026	14.5	.187	4	50 lbs.	100	3,000	0.60	Light Heavy Duty
14500X	05126	14.5	.187	4	50 lbs.	1,000	3,000	0.60	
18500	05091	17.75	.187	5	50 lbs.	100	2,000	0.72	
81200	05092	8	.300	2	120 lbs.	100	2,000	0.60	Heavy Duty
81200X	05086	8	.300	2	120 lbs.	1,000	2,000	0.60	
111200	05093	11	.300	3	120 lbs.	100	2,000	0.88	
141200	05027	15	.300	4 3/8	120 lbs.	100	2,000	1.28	
181750	05035	17.75	.315	5 1/4	175 lbs.	50	500	1.53	Extra Heavy Duty
241750	05030	24	.315	7 1/4	175 lbs.	50	500	2.56	
301750	05034	30	.354	9 1/4	175 lbs.	50	500	3.18	
361750	05032	36	.354	10 3/8	175 lbs.	50	500	3.86	
481750	05033	48	.354	15	175 lbs.	50	500	5.28	
601750	04195	59	.354	18 1/4	175 lbs.	50	500	6.00	
152500	05095	15	.500	4 3/8	250 lbs.	50	500	2.57	Extra Heavy Duty
182500	05096	18.87	.500	5 1/2	250 lbs.	50	500	3.09	
222500	05097	22.87	.500	6 7/8	250 lbs.	50	500	3.70	
282500	05098	28.75	.500	8 7/8	250 lbs.	50	500	4.53	
342500	05099	34.68	.500	10 1/2	250 lbs.	50	500	5.63	
402500	05088	40.5	.500	12 1/2	250 lbs.	50	500	6.60	