



Turnlok® Devices

Receptacles, Connectors, Plugs, Inlet, Outlet


3 Wire Grounded 15A, 125V




4710




4700




4792




15 Amp Connector




15 Amp Plug



4720-SSAN



4716-SS



4715-SS

Catalog Number	Rating A. V.	Description/Color	Cord Diameter	NEMA Config. No.	3rd Party Compliance		
					UL498	FSUL WC596	CSA
Receptacles							
4710	15 125	Single Receptacle		L5-15R	•	•	•
4700	15 125	Duplex Receptacle		L5-15R	•	•	•
4792	15 125	Combination Straight Blade and Locking		5-15R & L5-15R	•	•	•
Connectors IP20 Suitability							
L515-C	15 125	Black Shell, Yellow Face	.230"-.690"	L5-15R	•	•	•
★ L515-CCN	15 125	Black Shell, Yellow Face	.230"-.690"	L5-15R	•	•	•
CRL515-C	15 125	Corrosion Resistant	.230"-.690"	L5-15R	•	•	•
Plugs IP20 Suitability							
L515-P	15 125	Black Shell, Yellow Face	.230"-.690"	L5-15P	•	•	•
★ L515-PCN	15 125	Black Shell, Yellow Face	.230"-.690"	L5-15P	•	•	•
CRL515-P	15 125	Corrosion Resistant	.230"-.690"	L5-15P	•	•	•
4720-SSAN	15 125	Angle	.230"-.625"	L5-15P	•	•	•
Flanged Inlet & Outlet							
4716-SS	15 125	Flanged Inlet		L5-15P	•	•	•
4715-SS	15 125	Flanged Outlet		L5-15R	•	•	•
★ Denotes Canadian catalog number. All Canadian products have Combination Slotted/Robertson Head Brass Screws.							

2-Pole 3-Wire

All devices listed on this page conform to NEMA WD-1.



NEMA L5-15R



NEMA L5-15P



NEMA 5-15R

Catalog Number	Description	Catalog Number	Description
Accessories			
L15-RBC	Weatherproof Boot, Connector	S7	Stainless Steel Plate—4710
L15-RBP	Weatherproof Boot, Plug	S8	Stainless Steel Plate—4700/CR4700/4792
3720-FS	*Weatherproof Cover—4710	FC22-GL	+EHU-Strain Relief Grip
WP7	*Weatherproof Cover—4710	FC30-GL	+EHU-Strain Relief Grip
3710-FS	*Weatherproof Cover—4700	FC40-GL	+EHU-Strain Relief Grip
WP8	*Weatherproof Cover—4700	FC52-GL	+EHU-Strain Relief Grip
WPG1	*Weatherproof Cover for Flanged Inlet and Outlet	PSLD	Lockout Device

*For further information consult the Weatherproof Section R.

+For further information consult the Flexcor® Section K.

Turnlok® Devices Plugs & Connectors

Product Specifications & Performance

Pass & Seymour
 legrand

15 Amp Turnlok Plugs & Connectors

	Standard Product	Corrosion Resistant
Plugs		
Back Body	Nylon	Nylon
Front Body	Nylon	Nylon
Terminal Chamber	Polycarbonate	Polycarbonate
Cord Clamp	Nylon	Nylon
Insert	Nylon	Nylon
Blades	Brass	Nickel-Plated Brass
Terminal Clamp	Zinc-Plated Steel	Nickel-Plated Steel
Terminal Screws	Nickel- or Brass-Plated Steel	Nickel-Plated Steel
Ground Screws	Nickel-Plated Steel	Nickel-Plated Steel
Cord Clamp Screws	Nickel-Plated Steel	Nickel-Plated Steel
Assembly Screws	Nickel-Plated Steel	Nickel-Plated Steel
Connectors		
Back Body	Nylon	Nylon
Front Body	Nylon	Nylon
Terminal Chamber	Polycarbonate	Polycarbonate
Cord Clamp	Nylon	Nylon
Insert	Nylon	Nylon
Contacts	Brass	Nickel-Plated Brass
Terminal Clamp	Zinc-Plated Steel	Nickel-Plated Steel
Terminal Screws	Nickel- or Brass-Plated Steel	Nickel-Plated Steel
Ground Screws	Nickel-Plated Steel	Nickel-Plated Steel
Cord Clamp Screws	Nickel-Plated Steel	Nickel-Plated Steel
Assembly Screws	Nickel-Plated Steel	Nickel-Plated Steel
Performance		
Electrical		
Dielectric Withstand Voltage	1600V. minimum	
Maximum Working Voltage	277VAC	
Current Interrupting	Certified for current interrupting at full rated current	
Temperature Rise	30°C maximum after 50 cycles at 150% rated current	
Mechanical		
Cord Accommodations	Round portable service cords of diameters in accordance with the device rating as defined in UL62	
Cord Grip Accommodations	.230"-.690" diameter	
Terminal Identification	Green=Ground, White=Neutral, Brass=Hot	
Terminal Accommodation	#18 AWG min. - #10 AWG max.	
Product Identification	Amperage/Voltage, 3rd Party Listing, NEMA configuration	
Environmental		
Flammability	UL94 V2	
Operating Temperature	Maximum Continuous: 75°C Minimum: -40°C without impact	