



LIQUID TIGHT CONNECTORS

COMPONENT TYPE



| CAT# | A | B | C |
|----------|-------|-------|------|
| 470/470i | 1.446 | 1.260 | .400 |
| 471/471i | 1.500 | 1.385 | .420 |
| 472/472i | 1.603 | 1.720 | .420 |
| 473/473i | 1.792 | 1.900 | .550 |
| 474/474i | 1.900 | 2.290 | .546 |
| 475/475i | 1.737 | 2.633 | .520 |
| 476/476i | 2.080 | 3.156 | .585 |
| 477 | 3.025 | 4.205 | .775 |
| 478 | 3.530 | 4.910 | .920 |
| 479 | 3.660 | 5.470 | .920 |
| 480 | 3.875 | 5.925 | .987 |



| CAT# | A | B | C |
|----------|-------|-------|------|
| 490/490i | 2.062 | 2.340 | .52 |
| 491/491i | 2.220 | 2.340 | .52 |
| 492/492i | 2.550 | 3.550 | .68 |
| 493/493i | 2.820 | 3.785 | .67 |
| 494/494i | 3.362 | 3.960 | .70 |
| 495/495i | 3.450 | 4.130 | .70 |
| 496/496i | 4.036 | 4.700 | .57 |
| 497 | 5.215 | 5.375 | .77 |
| 498 | 6.100 | 6.500 | 1.10 |
| 499 | 6.715 | 7.450 | 1.10 |
| 500 | 6.780 | 8.00 | 1.10 |

ZINC DIE CAST

| TOPAZ CAT # | UPC# | CONDUIT SIZE | UNIT CTN | SHIP CASE | WT/ CASE |
|-----------------|-------|--------------|----------|-----------|----------|
| STRAIGHT | | | | | |
| 470 | 14250 | 3/8" 1/2" KO | 20 | 200 | 36 |
| 471 | 14260 | 1/2" | 20 | 200 | 40 |
| 472 | 14270 | 3/4" | 10 | 100 | 23 |
| 473 | 14280 | 1" | 5 | 50 | 20 |
| 474 | 14290 | 1 1/4" | 5 | 50 | 30 |
| 475 | 14300 | 1 1/2" | 2 | 20 | 15 |
| 476 | 14310 | 2" | 2 | 20 | 24 |
| 477* | 14320 | 2 1/2" | - | 1 | 1 |
| 478* | 14330 | 3" | - | 1 | 2 |
| 479* | 14340 | 3 1/2" | - | 1 | 3 |
| 480* | 14350 | 4" | - | 1 | 4 |



E170258

STRAIGHT WITH INSULATED THROAT

| | | | | | |
|------|-------|--------------|----|-----|----|
| 470i | 14360 | 3/8" 1/2" KO | 20 | 200 | 40 |
| 471i | 14370 | 1/2" | 20 | 200 | 34 |
| 472i | 14380 | 3/4" | 10 | 100 | 25 |
| 473i | 14390 | 1" | 5 | 50 | 22 |
| 474i | 14400 | 1 1/4" | 5 | 50 | 34 |
| 475i | 14410 | 1 1/2" | 2 | 20 | 18 |
| 476i | 14420 | 2" | 2 | 20 | 28 |



E170258

90° ANGLE

| | | | | | |
|------|-------|--------------|----|-----|----|
| 490 | 14610 | 3/8" 1/2" KO | 10 | 100 | 27 |
| 491 | 14620 | 1/2" | 10 | 100 | 28 |
| 492 | 14630 | 3/4" | 10 | 100 | 38 |
| 493 | 14640 | 1" | 5 | 50 | 32 |
| 494 | 14650 | 1 1/4" | 2 | 20 | 20 |
| 495 | 14660 | 1 1/2" | 2 | 20 | 26 |
| 496 | 14670 | 2" | 1 | 10 | 19 |
| 497* | 14680 | 2 1/2" | - | 1 | 4 |
| 498* | 14690 | 3" | - | 1 | 5 |
| 499* | 14700 | 3 1/2" | - | 1 | 6 |
| 500* | 14710 | 4" | - | 1 | 7 |



E170258

90° ANGLE WITH INSULATED THROAT

| | | | | | |
|------|-------|--------------|----|-----|----|
| 490i | 14720 | 3/8" 1/2" KO | 10 | 100 | 30 |
| 491i | 14730 | 1/2" | 10 | 100 | 27 |
| 492i | 14740 | 3/4" | 10 | 100 | 39 |
| 493i | 14750 | 1" | 5 | 50 | 33 |
| 494i | 14760 | 1 1/4" | 2 | 20 | 21 |
| 495i | 14770 | 1 1/2" | 2 | 20 | 26 |
| 496i | 14780 | 2" | 1 | 10 | 20 |



E170258

*2 1/2" - 4" Straight and 90° all insulated throat